


24643 TYBIA LED 38W-NW-SE B

Ceiling-mounted LED light fitting



Kanlux TYBIA LED is a general lighting luminaire using SMD diodes. When mounted in corridors, staircases, social or utility rooms, TYBIA LED allows for significant savings related to both reduced energy consumption and the long-term maintenance-free operation.

GENERAL DATA:

Colour: black
Place of assembly: ceiling mounted
Place of application: Indoors
Minimum distance from the illuminated object: 0,5m
Compatible with a dimmer: no
Wykrywanie ruchu: yes
Replaceable light source: no
Length [mm]: 410
Width [mm]: 410
Height [mm]: 61
Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC
Rated frequency [Hz]: 50
Maximum power [W]: 38
Class of protection against electric shock: I
Lampshade material: PMMA
Diode type: LED SMD
Luminous flux [lm]: 3800
Colour temperature: white
Correlated colour temperature [K]: 4000
Colour consistency in McAdam ellipses: ≤6
Colour rendering index: 80
Service life [h]: 30000
Number of on/off cycles: ≥20000
Lighting angle [°]: 110
Luminous efficiency of the lamp [lm/W]: 100
Ambient temperature range to which the product can be exposed: 5÷25
Enclosure material: aluminum alloy
Sensor type: microwave
Connection type: Self-clamping block
Range of sections of wires used [mm²]: 1-2,5
Lamp-heating time [s]: ≤1
Lamp-ignition time [s]: ≤0,5
IP class: 20