


33511 XLED G125 11W-WW

LED light source



Kanlux XLED GLOBE are large, decorative light sources. They look great in open luminaires or in pendants with no lampshades. Kanlux XLED GLOBE sources have a very high luminous efficacy and a wide beam angle (320 degrees), so a single light source can effectively illuminate a room.

GENERAL DATA:

Colour: white

Lamp designed for decorative lighting: Not applicable

Compatible with a dimmer: no

Height [mm]: 178

Diameter [mm]: 125

Depth [mm]: 125

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Lampshade material: glass

Light source: G125

Diode type: LED FILAMENT

Total rated luminous flux [lm]: 1520

Colour temperature: Warm white

Correlated colour temperature [K]: 2700

Colour consistency in McAdam ellipses: ≤ 6

Colour rendering index: 80

Rated lamp-service life [h]: 15000

Number of on/off cycles: ≥ 25000

Rated beam angle [°]: 320

Rated light level [°]: 320

Lamp rated current [mA]: 85

Ignition time [s]: $\leq 0,5$

Lamp-heating time to 60% of the full luminous flux [s]:
Negligible

Lamp-heating time to 95% [s]: < 2

Lamp premature-failure indicator: $< 5\%$ po 1000h

Lamp service life factor after the period of 6000h [%]:
 ≥ 90

Luminous flux retention factor at the end of rated service life [%]: ≥ 70

Luminous flux retention factor after the period of 6000h [%]: ≥ 80

Declaration of equality in power rating [W]: 99

Rated useful luminous flux [lm]: 1520

Light source shape: globe

LED light source

