


LED light source



Exceptional, decorative bulbs Kanlux XLED MIRROR provide decorative silver light. Part of the bubble is a mirror coating that will blend in perfectly as an addition to modern designs. The light in Kanlux XLED MIRROR is reflected upwards with a reflective layer, providing less direct light and creating a cosy atmosphere. It is perfect for lamps with an exposed bulb as an additional decoration or for lamps with a lampshade, where we can achieve the effect of subdued, romantic light.

GENERAL DATA:

Lamp designed for decorative lighting: Not applicable
Compatible with a dimmer: no
Height [mm]: 108
Diameter [mm]: 60
Depth [mm]: 60

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC
Rated frequency [Hz]: 50
Material: glass
Light source: A60
Diode type: LED FILAMENT
Total rated luminous flux [lm]: 680
Useful luminous flux of the light source Φ_{use} [lm]: 680
Useful luminous flux of the light source Φ_{use} [lm]: in sphere (360°)
Colour temperature: white
Correlated colour temperature [K]: 4000
Colour consistency in McAdam ellipses: ≤ 6
Colour rendering index: 80
Rated lamp-service life [h]: 15000
Number of on/off cycles: ≥ 15000
Rated beam angle [°]: 150
Rated light level [°]: 150
Lamp rated current [mA]: 40
Annual power consumption [kWh/1000h]: 7
Ignition time [s]: $\leq 0,5$
Lamp-heating time to 60% of the full luminous flux [s]: Negligible
Lamp-heating time to 95% [s]: < 2
Lamp premature-failure indicator: $< 5\%$ po 1000h
Lamp service life factor after the period of 6000h [%]: ≥ 90
Luminous flux retention factor at the end of rated

33515 XLED A60 M 7W-NW

LED light source



service life [%]: ≥ 70

Luminous flux retention factor after the period of 6000h [%]: ≥ 80

Declaration of equality in power rating [W]: 52

Light source shape: standard

