


Ducted fan



### GENERAL DATA:

**Colour:** white  
**Place of assembly:** Recessed mount in the wall  
**Place of application:** Indoors  
**Time switch:** yes  
**Length [mm]:** 158  
**Width [mm]:** 79  
**Height [mm]:** 158  
**Assembly hole [mm]:** Ø100

### TECHNICAL DATA:

**Rated voltage [V]:** 220-240 AC  
**Rated frequency [Hz]:** 50/60  
**Maximum power [W]:** 19  
**Class of protection against electric shock:** II  
**Engine rotation:** 2550  
**Bearing type:** ball-type  
**Connection type:** Terminal block  
**Range of sections of wires used [mm<sup>2</sup>]:** 1  
**Sound pressure [dB]:** 39.5  
**Air-flow volume rate [m<sup>3</sup>/h]:** 100  
**Motor-power consumption [W]:** 19  
**IP class:** X4  
**Protection class:** II

### ADDITIONAL INFORMATION:

- Product available only to the customers of Kanlux Czech Republic
- Rotation speed: 2550/min
- Efficiency 100m<sup>3</sup>/h
- Noise level 39,5dB (A)
- AERO DK100L, equipped with an indicator light / AERO RK100, equipped with an indicator light, a pull switch and cord with a plug / equipped with an indicator light and a timer