


Surface-mounted LED office fixture



### GENERAL DATA:

**Colour:** white  
**Place of assembly:** ceiling mounted  
**Place of application:** Indoors  
**Minimum distance from the illuminated object:** 0,5m  
**Compatible with a dimmer:** no  
**The product is not suitable to be covered with a heat-insulating material:** yes  
**Length [mm]:** 1200  
**Width [mm]:** 300  
**Height [mm]:** 35  
**Integrated LED light source:** yes

### TECHNICAL DATA:

**Rated voltage [V]:** 220-240 AC  
**Rated frequency [Hz]:** 50  
**Maximum power [W]:** 40  
**Class of protection against electric shock:** I  
**Lampshade material:** plastic  
**Diode type:** LED SMD  
**Luminous flux [lm]:** 4400  
**Colour temperature:** white  
**Correlated colour temperature [K]:** 4000  
**Colour consistency in McAdam ellipses:**  $\leq 3$   
**Colour rendering index:** 80  
**Service life [h]:** 50000  
**Luminous-flux-retention factor at the end of rated service life:** L90B10  
**Number of on/off cycles:**  $\geq 30000$   
**Lighting angle [°]:** X90/Y95  
**Luminous efficiency of the lamp [lm/W]:** 110  
**Ambient temperature range to which the product can be exposed:** 5÷25  
**Shade type:** m-type microprismatic  
**Enclosure material:** Metal  
**Connection type:** Self-clamping block  
**Range of sections of wires used [mm<sup>2</sup>]:** 1,5÷2,5  
**Lamp-heating time [s]:**  $\leq 1$   
**Lamp-ignition time [s]:**  $\leq 0,5$   
**IP class:** 20

### ADDITIONAL INFORMATION:

- 5 years Warranty under the terms of the warranty statement, available on our website