

Kanlux

Kanlux STONO N


- в комплекта проводник 3 м
-



IP
65

MODERN
design

[V] 220-240 AC	[Hz] 50			IP 65		
UK CA						



STONO 20 N



Диаметър [mm]



STONO 20 N	24654	max 15	200	GLS/CFL/LED	E27	гранит
STONO 30	24651	max 25	300	GLS/CFL/LED	E27	гранит
STONO 390 N	36591	max 20	390	GLS/CFL/LED	E27	гранит
STONO 490 N	36592	max 20	490	GLS/CFL/LED	E27	гранит
STONO 585 N	36593	max 20	585	GLS/CFL/LED	E27	гранит
STONO 780 N	36594	max 20	780	GLS/CFL/LED	E27	гранит



STONO 20 N



STONO 30



STONO 390 N




STONO 490 N




STONO 585 N




STONO 780 N




STONO 20 N




STONO 30




STONO 390 N



STONO 490 N



STONO 585 N



STONO 780 N

Date of issue: 16.03.2026, 12:45

Запазва се правото за въвеждане на технически промени. Данните, съдържащи се в този материал, не са правно обвързващи.

Фотометрия: резултати, получени по време на изпитване на дадения екземпляр.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

BG